


air-duct flange connection



Self Adhesive elastomeric foam gasket tape for air-duct flange connection

ESCOTAPE is an elastomeric closed

cell self-adhesive foam gasket tape for cooling and heating air-duct joint connections to prevent air leakage, reduce vibration/noise and also serves as thermal insulation to prevent condensation and heat transfer. With acrylic pressure sensitive adhesive, Escotape is easily installed on the surface of the connection joint.



AVERAGE SPECIFICATION:

AVERAGE SPECIFICATION :					
MATERIAL	:	Closed cell foam			
COLOR	:	Black			
DENSITY	:	3-5 lbs/ft ³ (0.048-0.080 g/cm ³)			
HARDNESS	:	40-60 shore C2			
WATER ABSORPTION	:	Less than 10 % by weight			
COMPRESSION DEFLECTION	:	6-8 PSI			
TENSILE STRENGTH	:	More than 60 PSI (4.2 kg/cm ²)			
ELONGATION AT BREAK	:	More than 200%			
SERVICE TEMPERATURE	:	-40°F to 220°F (-40°C to 105°C)			
THERMAL CONDUCTIVITY		0.35 BTU. in/ft ² h F at 75 F			
		(0.050 W/mK at 24°C)			
FLAMMABILITY	:	Class HB UL-94			
		B2 DIN 4102			
ADHESIVE TYPE	:	Acrylic Pressure Sensitive Adhesive			
INITIAL TACK	:	3.0 cm (Ball 15/16")			

STANDARD SIZE & PACKING

Code	Description	Packing	Carton
TPEC051510	ESCOTAPE 5 mm x 15 mm x 10 m	32 rolls	26 (H) x 29 x57.5 cm. 20' = 720 cartons 40' = 1,500 cartons
TPEC052010	ESCOTAPE 5 mm x 20 mm x 10 m	24 rolls	
TPEC053210	ESCOTAPE 5 mm x 32 mm x 10 m	14 rolls	
TPEC054010	ESCOTAPE 5 mm x 40 mm x 10 m	12 rolls	

Other size are available upon request.



บริษัท ก็อป อินซูเลชั้น แอนด์ เกรดตั้ง จำกัด 7/1 ซอยเพชรเกษม 108 เยก 9 ก.เพยรเกษม เขวงหนองค้างพลู เชตหนองเชม กรุงเกพ 10160 Tel. 02 808 2147-8 Fax. 02 808 3457